

## Information: Dry Ice Containers



### Technical specification of the Dry Ice Container Type 160:

<b>Measurements of the corpus:</b>	outside: 870 x 570 x 1030mm (LxWxH) inside: 660 x 360 x 700mm (LxWxH)
<b>Weight of the Container:</b>	ca. 56kg
<b>Capacity 3mm Pellets:</b>	ca. 120kg
<b>Capacity Blocks:</b> (150x150mm)	ca. 200kg
<b>Material container:</b>	GFRP = Glass-fibre-reinforced plastic two-component insulation foam Gel-Code surface
<b>Material frame:</b>	2,5mm metal, galvanized
<b>Lock:</b>	Release fastener, galvanized, suitable for lead sealing
<b>Hinge:</b>	Safety Hinge, decelerated

## Technical specification of the Dry Ice Container Type 260:

<b>Measurements of the corpus:</b>	outside: 860 x 860 x 980mm (LxWxH) inside: 650 x 650 x 630mm (LxWxH)
<b>Weight of the Container:</b>	ca. 76kg
<b>Capacity 3mm Pellets:</b>	ca. 230kg
<b>Capacity Blocks:</b> (150x150mm)	ca. 320kg
<b>Material container:</b>	GFRP = Glass-fibre-reinforced plastic two-component insulation foam Gel-Code surface
<b>Material frame:</b>	2,5mm metal, galvanized
<b>Lock:</b>	Release fastener, galvanized, suitable for lead sealing
<b>Hinge:</b>	Safety Hinge, decelerated

## Technical specification of the Dry Ice Container Type 440:

<b>Measurements of the corpus:</b>	outside: 1200 x 800 x 1100mm (LxWxH) inside: 990 x 590 x 720mm (LxWxH)
<b>Weight of the Container:</b>	ca. 84kg
<b>Capacity 3mm Pellets:</b>	ca. 350kg
<b>Capacity Blocks:</b> (150x150mm)	ca. 550kg
<b>Material container:</b>	GFRP = Glass-fibre-reinforced plastic two-component insulation foam Gel-Code surface
<b>Material frame:</b>	2,5mm metal, galvanized
<b>Lock:</b>	Release fastener, galvanized, suitable for lead sealing
<b>Hinge:</b>	Safety Hinge, decelerated

## Technical specification of the Dry Ice Container Type 520:

<b>Measurements of the corpus:</b>	outside: 1160 x 1050 x 1000mm (LxWxH) inside: 955 x 850 x 645mm (LxWxH)
<b>Weight of the Container:</b>	ca. 93kg
<b>Capacity 3mm Pellets:</b>	ca. 390kg
<b>Capacity Blocks:</b> (150x150mm)	ca. 600kg
<b>Material container:</b>	GFRP = Glass-fibre-reinforced plastic two-component insulation foam Gel-Code surface
<b>Material frame:</b>	2,5mm metal, galvanized
<b>Lock:</b>	Release fastener, galvanized, suitable for lead sealing
<b>Hinge:</b>	Safety Hinge, decelerated

## Options:

In addition to the options listed here, we can also customize the containers to meet your personal needs.

Pos.	Item No.	Description
10	Option 1	Customer Label in transport frame, lasered
11	Option 2	Frame with wheels as adaptation for bases
12	Option 3	Wheels instead of 4 bases two times steerable, braked or unbraked
13	Option 3.1	Wheels instead of 4 bases four times steerable, braked or unbraked
14	Option 4	Bases made of high performance plastic
15	Option 5	Riveted safety plates for stacking the containers
16	Option 6	Riveted metal protection for the edges of the container
17	Option 7	Surface refinement, multicoloured
18	Option 8.1	Safety cladding, metal 0,8 mm, with recess for the Label plate
19	Option 8.1	Safety cladding, metal 0,8 mm, without recess for the Label plate